

B 260 RI BP

The ride-on scrubber drier B 260 RI Bp, which is equipped with 260 l tanks and has been developed for the toughest industrial applications, with its driving speed of up to 10 km/h.



Made in Europe



Order no.

1.480-257.0

- Adjustable brush contact pressure
- EASY Operation selector switch
- Scrubbing and sweeping in one go

Technical data

EAN code		4054278954356
Drive type		Battery
Traction drive		Traction motor
Working width of brushes	cm	100 - 120
Working width, vacuuming	cm	114 - 134
Tank of fresh/dirty water		260 / 260
Theoretical area performance	m²/h	max. 12000
Practical area performance	m²	8400
Battery	V	36
Driving speed	km/h	max. 10
Climbing ability	%	max. 15
Brush contact pressure	kg	150
Aisle turning width	cm	212
Water consumption	l/min	max. 9
Sound pressure level	dB(A)	73
Total permissible weight	kg	1840
Weight without accessories	kg	499
Dimensions (L × W × H)	mm	1950 × 1040 × 1570

Equipment

Auto Fill	■
Patented tank rinsing system	■
Powerful traction drive	■
Automatic water stop	■
Parking brake	■
Adjustable steering wheel	■
Solenoid valve	■
Squeegee, curved	■
2-tank system	■
standard daytime driving light	■
Type of suction lips	Linatex®
Kärcher colour and operating concept	■
Kärcher Intelligent Key System (KIK) with over 30 user languages and individual user rights	■
Home Base fastening possibilities for mop or similar	■
speed reduction in curves for increased safety	■
electrical and mechanical float switch	■
Easy Operation selector switch	■

■ included in delivery.

Users must receive training on this device.



Newly developed roller brush head

- Greatly improved sweeping results and prevents squeegee blockages.
- The rollers can be changed in a matter of seconds and without tools.
- Excellent cleaning results.



10 km/h driving speed

- Enables a high area performance in next to no time and quick transportation operations.
- The steering angle sensor acts as a safety feature when driving in curves.
- There is automatic braking if speed is too high when driving in curves.



Includes two turbines as standard

- Excellent vacuuming results on all surfaces.
- Wear-free Ec turbines.
- Optimised airflow with the newly developed squeegee.

EQUIPMENT FOR B 260 RI BP

1.480-257.0



		Order no.	Description	
SUCTION BARS AND SQUEEGEES				
Suction bar, complete				
Suction bar parabolic B250R Industrial, 1140 mm	1	4.777-104.0		<input type="checkbox"/>
Suction bar parabolic 1340mm/53in Indust, 1340 mm	2	4.777-110.0		<input type="checkbox"/>
BRUSH HEADS				
Brush-head R 100/ 39"	3	2.763-056.0		<input type="checkbox"/>
Brush-head D 100/ 39"	4	2.763-057.0		<input type="checkbox"/>
Brush-head R 120 Industrie	5	2.763-058.0		<input type="checkbox"/>
KITS				
Side broom/SSD mounting kit				
Add-on kit side scrubbing deck B260RI	6	2.644-373.0		<input type="checkbox"/>
Fleet mounting kit				
Add-on kit	7	2.644-391.0		<input type="checkbox"/>
Other attachment kits				
Add-on kit spraying nozzle B 250	8	2.644-392.0		<input type="checkbox"/>
Add-on kit ram protection suction bar	9	2.644-369.0		<input type="checkbox"/>
Add-on kit connection HD	10	2.644-370.0		<input type="checkbox"/>
Protective roof	11	2.643-849.0	This high-quality protective roof for the B 250 R scrubber drier (height 2,170 mm including protective roof) protects the operator from falling objects - tested in accordance with EN IEC 60335-2-72.	<input type="checkbox"/>
Dose mounting kit				
Add-on kit metering cleaning agents B260	12	2.644-368.0		<input type="checkbox"/>
Lighting/RKL mounting kit				
Add-on kit revolving signal light B 260	13	2.644-363.0		<input type="checkbox"/>
Add-on kit BlueSpot front B260RI	14	2.644-366.0		<input type="checkbox"/>

■ Included in delivery. □ Available accessories.

EQUIPMENT FOR B 260 RI BP
1.480-257.0



		Order no.	Description	
KITS				
Lighting/RKL mounting kit				
Add-on kit BlueSpot rear B260RI	15	2.644-367.0		<input type="checkbox"/>
TRACTION BATTERIES AND CHARGERS				
Batteries				
Battery kit with loader 525Ah/36V Li-Ion	16	2.654-000.0		<input type="checkbox"/>
Battery kit wet 1x 36V/630Ah, 36 V, 630 Ah, low maintenance	17	2.815-108.0		<input type="checkbox"/>
Battery Chargers				
Battery charger for replacement 36V 65A, 36 V	18	4.035-191.0		<input type="checkbox"/>
BC cpl. offp 38,4/200A 380V/50-60Hz	19	4.654-083.0		<input type="checkbox"/>

■ Included in delivery. □ Available accessories.